

LED Lamps

360° or 180° Directable

LED Conversions, Inc.

50B Northwestern Drive, Suite 10
Salem, NH 03079

Phone: 603-898-1144

Fax: 603-218-6086



Our LED Lamps are the environmentally preferred alternative to traditional metal halide lamps. These amazing lamps guarantee huge energy savings with seven models consuming just 15-110 watts, replacing 50-400 watt lamps. Other wattage lamps are available dependent on the application.

A maintenance free and cost-effective solution for use in illuminating facades, landscapes, displays, parking areas, schools, office buildings, shopping plazas, apartment complexes and more.

It's the ideal retrofit for bollard, post-top, shoebox, wall pack, canopy, flood, cobra head, gooseneck, high bay and recessed can fixtures.

Features

- 50,000+ hours per DOE testing at up to 126 lumens per watt
- 5 Yr. Manufacturers registered warranty
- Maintenance Free
- Return on Investment between 18 and 40 months
- Green Product

Environmental

- Contains no Mercury or Lead
- Does not produce UV Rays

Ask about Listing for Incentives

Specifications

MODEL	GKS28 15W 360°	GKS28 24W 360°	GKS28 45W 360°	GKS28 54W 360°	GKS38 40W 180°	GKS38 60W 180°	GKS35 110W 180°
Replaces	50-70W	100W	175W	250W	175W	250W	400W
Watts	15w	24w	45w	54w	40w	60w	110w
Input Voltage	100 - 277VAC 50-60 Hz	100 - 277VAC 50-60 Hz	100 - 277VAC 50-60 Hz	100 - 277VAC 50-60 Hz	100 - 277VAC 50-60 Hz	100 - 277VAC 50-60 Hz	100 - 277VAC 50-60 Hz
Lm Efficacy	133 Lm/W	130 Lm/W	126 Lm/W	120 Lm/W	113 Lm/W	104 Lm/W	102 Lm/W
Lumens	2,000LM ±200	3,100LM ±200	5,600LM ±200	6,450LM ±200	4,525LM ±200	6,211LM ±200	11,240LM ±200
CRI	80+	80+	84+	84+	84+	84+	84+
Color Temp	5000k Standard 3k - 6k Available upon request	5000k Standard 3k - 6k Available upon request	5000k Standard 3k - 6k Available upon request	5000k Standard 3k - 6k Available upon request	5000k Standard 3k - 6k Available upon request	5000k Standard 3k - 6k Available upon request	5000k Standard 3k - 6k Available upon request
Power Factor	>0.90	>0.90	>0.93	>0.93	>0.92	>0.92	>0.97
THD	<19%	<19%	<19%	<19%	<19%	<19%	<19%
L70 Lifetime	50,000H	50,000H	50,000H	50,000H	50,000H	50,000H	50,000H
Base	E26 / E39	E26 / E39	E26 / E39	E26 / E39	E26 / E39	E39	E39
Dimensions Dia. x Height	2.52" x 5.7"	2.52" x 7.52"	3.43" x 10.75"	3.43" x 10.75"	3.54" x 8.5"	3.54" x 10.75"	4.44" x 10.75" Folds out to 9" x 10.75"

- Environment: Suitable for totally enclosed fixtures
- Operating Temperature: -22°F - +140°F
- Lumen maintenance at 6,000 hours: 98.28%
- IP Rating: IP64
- Surge protection: 4kv high surge protection
- Housing: Die cast aluminum
- Lens type: Clear (frosted available upon request)
- AC 120v-277v direct (Disconnect ballast)
- Warranty: 5 years

